



# 9000 SERIES GLOSS ENAMEL PAINT

Technical Data Sheet

## GENERAL DESCRIPTION

A solvent based alkyd enamel paint that is easy to apply and gives a smooth, high gloss and durable finish.

## RECOMMENDED USES

Suitable for use on wood and metal in both interior and exterior applications.

## FEATURES

- Excellent gloss & gloss retention
- Superior hiding & film build
- Good durability & fungus resistance

## TECHNICAL SPECIFICATION

Finish	Gloss
Theoretical Coverage	14-18 m <sup>2</sup> /litre
Recommended Dry Film Thickness	30-40 microns
Drying Time	Touch dry: 1.5 hours at 30°C Hard dry: 7 hours at 30°C
Recoating Interval	7 hours minimum
Thinner	White spirit

## APPLICATION METHOD & DILUTION

Brush	Ready for use. Dilute up to 10% if necessary.
Roller	Ready for use. Dilute up to 10% if necessary.
Conventional Air Spray	Dilute 10 - 20%.
Airless Spray	Ready for use.

The information contained herein with is accurate and reliable to our best knowledge. Therefore, no implied conditions, warranties or other terms will apply to the Product. We do not and cannot warrant the results which the user may obtain by using the product to meet any particular requirements.



## 9000 SERIES GLOSS ENAMEL PAINT

Technical Data Sheet

### **SURFACE PREPARATION**

Ensure the surface is dry and free from dirt, grease and all other poorly adhering contaminants. Sanding is recommended to smoothen uneven surfaces, remove rusts or previously painted surfaces.

### **STORAGE**

Containers must be tightly closed and kept in dry, cool and well-ventilated environments. Keep away from direct sunlight and ignition source.

### **PACKING SIZE**

1L & 5L

The information contained herein with is accurate and reliable to our best knowledge. Therefore, no implied conditions, warranties or other terms will apply to the Product. We do not and cannot warrant the results which the user may obtain by using the product to meet any particular requirements.